The Model 28 Receiving Selector converts incoming sequential (serial) teletypewriter signals into parallelwire intelligence.

Capable of operating at 60, 75 or 100 words per minute, this set has the built-in reliability and rugged durability which distinguishes all units in the Teletype Model 28 line of equipment.

The selector normally operates on a 5 level, start-stop code. Provisions have been made for 6 level operation if it is desired by the user.

The unit is equipped with two types of contacts – code reading and timing contacts.

In order to operate the set at the most favorable portion of a line signal, the selector is equipped with a range finder. This component is read by means of a range scale and is manually adjusted while the set is relaying signals to receiving apparatus.

In keeping with Model 28 specifications this unit needs lubrication only once every six months when operating at 100 words per minute. The interval is extended when slower speeds are used. Operating speed of the unit is changed by gear substitution.

Teletype applications specialists are at your service for more information on the Model 28 Receiving Selector. Get in touch with them soon.

MODEL 28 RECEIVING SELECTOR (TYPE LRS)

VIEW OF THE MODEL 28 RECEIVING SELECTOR WITH COVER.

TELETYPE MODEL 28 RECEIVING SELECTOR

TECHNICAL DATA

| WIDTH DEPTH HEIGHT WEIGHT | 0 1/2 INCHES 9 3/4 INCHES 8 INCHES 16 1/2 LBS | | | |
|------------------------------------|---|------------------------|-----------------------------|--|
| SIGNALING | INFUT, SERIAL (SEQUENTIAL) 5 OR 6 LEVEL. START-STOP, OUTPUT: PARALLEL-WIRE, 5 OR 6 LEVEL. INPUT CURRENT: 060 AMP. ± 10% D.C. SYNCHRONDUS, 65 WATT, 115 VOLT, 60 CYCLE, A.C. | | | |
| SPEED | OPERATIONS PER MINUTE | WORDS PER MINUTE | CHARACTERS PER SECOND | |
| | 368 450 600 | eo 75 100 | 6 D 7.8 10.0 | |
| | | | | |

FINISHES: AVAILABLE IN VARIOUS COLORS.



GENERAL OFFICES

5555 Touhy Avenue, Skokle, Illinois 425-13th Street, N.W. Phones: ORchard 6-1000, Skokie Washington 4, D.C. COrnella 7-6700, Chicago Phone: MEtropolitan 8-1016 **Direct Distance Dialing** Area Code 312

GOVERNMENT LIAISON OFFICE

TWX: 312-677-6700 (24-hour unattended service)

W. U. Service on premises TELEX: 02-5451

Teletype Corporation manufactures this equipment for the Bell System and others who require the utmost reliability from their message and data communications systems.